

Series BASIC METAL FREE / Safety Footwear

Characteristics and advantages:

- **Black micro fiber leather S3.**
- **"Metal Free".** Footwear without metallic components (except in welder model).
- Non-metallic **anti-perforation** and safety stop template.
- Maximum Polyurethane **Bidensity sole** anti-slip co-efficient SRC.

General applications:

General Use (Safety Footwear) and especially **jobs where there is a high incidence of humidity** (S3), work where **shoes without metal parts are required** (Metal Free), with a **high anti-slip co-efficient** (SRC) or needed **lighter footwear** (with non-metallic protections) and **more flexible** (with non-metallic anti-perforation insole).



1688-ZRE PRO
Mod. "TARRACO" 

Black leather shoe S3 "Metal Free" with dual density polyurethane sole

Category: S3 SRC WRU E A

CE EN20345

Sizes_ 36 to 47



METAL
Free



1688-ZREW
WOMAN PATTERN.

Sizes_ 34 to 41



1688-BSO PRO Mod. "ONUBA"



Black leather welder's boot with S3 buckle and double density polyurethane sole

Applications: Work related to welding processes and techniques posing risk of molten metal, sparks and incandescent projections in general.

Features and Advantages:

- Quick release buckle closure, meaning the boot can quickly be removed in the event of incandescent splashes, sparks...
- Anti-perforation insole and non-metallic safety stop.
- Polyurethane dual density sole maximum anti-slip SRC ratio.

Category: S3 SRC WRU E A

CE EN20345

Sizes_ 38 to 47



SAFETY
FOOTWEAR

1688-BRE PRO Mod. "SAGUNTO"



Black leather boot S3 "Metal Free" with dual density polyurethane sole

Category: S3 SRC WRU E A

CE EN20345

Sizes_ 36 to 47



**METAL
Free**



»»»»» Serie BASIC METAL FREE / Safety Footwear

Characteristics and advantages:

- Microfiber split leather combined with a **high performance fabric and high resistance to rips and tears**.
- **"Metal Free"**. Footwear without metallic components.
- **Non-metallic anti-perforation** and safety stop insole.
- Maximum Polyurethane **Bidensity sole** anti-slip co-efficient SRC.

General applications:

General Use (Safety Footwear) and in jobs where **footwear is required without non-conductive metal parts** (Metal Free), with a **high anti-slip co-efficient** (SRC) or a **lighter footwear** (with non-metallic protections) and **more flexible** (with anti-perforation non-metallic template).



1688-ZSRA PRO Mod. "HISPALIS"

Blue suede shoe S1P "Metal Free" with dual density polyurethane sole

Category: S1P SRC E A

CE EN20345

Sizes_ 35 to 47



METAL
Free



1688-BSPM PRO Mod. "EMERITA"

Brown suede boot S1P "Metal Free" with dual density polyurethane sole

Category: S1P SRC EA

CE EN20345

Sizes_ 38 to 47



METAL
Free



1688-ZSRM PRO Mod. "LUSITANIA"

Brown suede boot S1P "Metal Free" with dual density polyurethane sole

Category: S1P SRC EA

CE EN20345

Sizes_ 35 to 47



METAL
Free



Serie METAL BASIC / Safety Footwear

1688-B Mod. "MASTIA"



Black microfiber leather boot S1P with double density polyurethane sole

Applications: General use in multiple sectors and applications where a safety footwear (safety stop and anti-drilling template) is needed, such as construction, workshops, logistics, automotive and manufacturing and industry in general, with a high anti-slip co-efficient. Exceptional (SRC).

Features and Advantages:

- Black microfiber leather S1P.
- Safety stop and anti-perforation steel insole.
- Dual density polyurethane sole (comfort zone less density than the area of contact with the floor).

Category: S1P SRC E A

CE EN20345

Sizes_ 36 to 47



1688-Z Mod. "UXAMA"



Black micro fiber leather S1P shoe with double density polyurethane sole

Applications: General use in multiple sectors and applications where a safety footwear (safety stop and anti-drilling template) is needed, such as construction, workshops, logistics, automotive and manufacturing and industry in general, with a high anti-slip co-efficient. exceptional (SRC).

Features and Advantages:

- Black micro fiber leather S1P.
- Safety stop and anti-perforation steel insole.
- Dual density polyurethane sole (comfort zone less density than the area of contact with the ground).

Category: S1P SRC E A

CE EN20345

Sizes 36 to 47



1688-BSO Mod. "VULCANO"



Black microfiber leather boot S1P buckle welder with dual density polyurethane sole

Applications: Work related to welding processes and related techniques with the risk of splashing molten metals, sparks... and incandescent projections in general, with a high exceptional antislip co-efficient (SRC).

Features and Advantages:

- Quick detach buckle closure, allows quick removal of the boot in case of incandescent splashes, sparks, etc.
- Safety stop and anti-perforation steel insole.
- Dual density polyurethane sole (comfort zone less density than the area of contact with the floor).

Category: S1P SRC EA

CE EN20345

Sizes_ 38 to 47



1688-ZS Mod. "SCORPIO"



Gray perforated split suede leather shoe S1P with dual density polyurethane sole

Applications: General use in multiple sectors and applications where a safety footwear (safety cap and anti-drilling template) is needed in hot environments, such as construction, workshops, agriculture, logistics, automotive and manufacturing and industry in general, with a high exceptional anti-slip co-efficient (SRC).

Features and Advantages:

- Perforated suede microfiber leather combined with a high performance fabric and high resistance to rips and tears.
- Safety stop and anti-perforation steel insole.
- Dual density polyurethane sole (comfort zone less density than the area of contact with the floor).

Category: S1P SRC EA

CE EN20345

Sizes_ 36 to 47



**1688-ZS1
Anti-perforation Insole**



Sizes_ 36 to 47